Appl. No.: 10/506,370 Amdt. Dated May 20, 2009

Reply to Office Action of March 31, 2009

Amendments to the Claims:

1. (Previously Presented) A method of testing a mobile telephone terminal comprising the

steps of:

transmitting from a test apparatus to the terminal on a downlink a predetermined data

pattern which the terminal will recognise and which will prompt the terminal to transmit an

access request on an uplink,

the terminal receiving said predetermined data pattern and responding by transmitting an

access request to the test apparatus on the uplink,

the test apparatus receiving the access request and analyzing the access request to assess

the performance of the terminal based upon assessment of the access request alone, the test

apparatus transmitting said predetermined data pattern multiple times at different power levels, and the test apparatus analyzing each access request to determine a power level threshold at

which the terminal fails to transmit an access request.

2. (Original) A method as claimed in claim 1 in which multiple predetermined data patterns are

provided for testing the terminal under different operating conditions, each data pattern

prompting a different response from the terminal in transmitting an access request.

3. (Original) A method as claimed in claim 2 in which said multiple predetermined data

patterns are such that they each prompt the terminal to transmit an access request at a different

power level.

4. (Original) A method as claimed in claim 2 in which said multiple predetermined data

patterns are such that they each specify a different maximum number of times the terminal

should send an access request if the terminal receives a response to none of them.

5. (Canceled)

2 of 6

Appl. No.: 10/506,370 Amdt. Dated May 20, 2009

Reply to Office Action of March 31, 2009

6. (Previously Presented) A method as claimed in claim 1 in which said predetermined data

pattern is transmitted to the terminal on a cable connection.

7. (Original) A method as claimed in claims 1 in which said predetermined data pattern is

transmitted to the terminal over an air interface.

8. (Original) A method as claimed in claim 7 in which the air interface is screened from other

signals.

9. (Previously Presented) A method as claimed in claim 1 in which the access request is

analyzed by a power measurement.

10. (Previously Presented) A method as claimed in claim 1 in which the access request is

analyzed by a modulation quality measurement.

11. (Previously Presented) Test apparatus for testing a mobile telephone terminal, the test

apparatus being structured and arranged to transmit a predetermined data pattern on a downlink

to prompt a response from the terminal in the form of an access request on an uplink, the test

apparatus being structured and arranged to analyze the access request and produce a test result

based upon assessment of the access request alone, the test apparatus being adapted to vary the

power level at which said predetermined data pattern is transmitted and to analyze each access

request from the terminal to determine a power level threshold at which the terminal fails to

transmit an access request.

12. (Original) Test apparatus as claimed in claim 11 which generates multiple predetermined

data patterns for testing the terminal under different operating conditions of transmission power level and/or maximum number of access requests to be transmitted if there is no response to any

of them

3 of 6

Appl. No.: 10/506,370 Amdt. Dated May 20, 2009

Reply to Office Action of March 31, 2009

13. (Canceled)

14. (Previously Presented) Test apparatus as claimed in claim 11 which is connected to the

terminal to transmit said predetermined data pattern either by a cable connection or an air

interface.

15. (Previously Presented) Test apparatus as claimed in claim 11 which is adapted to analyze

the access request by making a power measurement.

16. (Previously Presented) Test apparatus as claimed in claim 11 which is adapted to analyze

the access request by making a modulation quality measurement.

17. (Previously Presented) Test apparatus for testing a mobile telephone terminal, the test

apparatus comprising a memory to store a predetermined data pattern and a transmitter to transmit said predetermined data pattern on a downlink to said mobile telephone terminal in

order to prompt a response from said mobile telephone terminal in the form of an access request

on an uplink to the test apparatus, a receiver to receive said access request on the uplink from the

terminal, and a processor to analyze said access request and produce an assessment of the

performance of the terminal based upon assessment of the access request alone, the test

apparatus being adapted to vary the power level at which said predetermined data pattern is

transmitted and to analyze each access request from the terminal to determine a power level

threshold at which the terminal fails to transmit an access request.

18. (Previously Presented) A method of testing a mobile telephone terminal comprising the

steps of:

transmitting from a test apparatus to the terminal on a downlink a predetermined data

pattern which the terminal will recognise and which will prompt the terminal to transmit an

access request on an uplink,

4 of 6

Appl. No.: 10/506,370

Amdt. Dated May 20, 2009

Reply to Office Action of March 31, 2009

the terminal receiving said predetermined data pattern and responding by transmitting to the test apparatus an access request,

the test apparatus receiving said access request and analyzing it to assess the performance of the terminal based upon assessment of the access request and without replying to the terminal in response to said access request, and

the test apparatus transmitting said predetermined data pattern multiple times at different power levels, and the test apparatus analyzing each access request to determine a power level threshold at which the terminal fails to transmit an access request.

19. (Currently Amended) Test apparatus as claimed in claim 11,—for testing a mobile telephone terminal comprising:

a memory for storing [[a]] the predetermined data pattern,

a generator for generating a signal corresponding to said predetermined data pattern on a downlink, said signal being adapted to be recognisable by the terminal and to trigger it to transmit an access request on an uplink, and

a detector for detecting and analyzing said access request to assess the performance of the terminal, and without replying to the terminal in response to said access request.

the test apparatus being adapted to vary the power level at which said predetermined data pattern is transmitted and to analyze each access request from the terminal to determine a power level threshold at which the terminal fails to transmit an access request.

20-25. (Canceled)